



Supported truss systems	QL40A	QD40A	QD30A
Main tubes	Extruded aluminium EN-AW 6082 T6 – Ø50x4	Extruded aluminium EN-AW 6082 T6 – Ø50x3	Extruded aluminium EN-AW 6082 T6 – Ø50x3
Crossways tubes	Extruded aluminium EN-AW 6082 T6 – Ø30x3	Extruded aluminium EN-AW 6082 T6 – Ø30x3	Extruded aluminium EN-AW 6082 T6 – Ø30x3
Connection system	Aluminium fork EN-AW 6082 T6	Aluminium plate EN-AC 47000	Aluminium plate EN-AC 47000
Max height as a tower [m]	12	9	7.2

Components	
Description	Weight
MTB40 Base in sheet aluminium EN-AW 5083 – 15 mm thickness + 4 stabilizer MTF40	166 Kg
MTT40F Top in aluminium alloy EN-AW 6082 T6 with two pulleys	17Kg
QL40A truss system (approx.)	12,5 Kg/m
QD40A truss system (approx.)	9,5 Kg/m
QD30A truss system (approx.)	8 Kg/m

These technical data are valid only for structures entirely assembled with Litec materials.

Date of issue 31/07/2008	Litec is a Brand of Staging Systems Europe S.p.A. www.litecruss.com - info@litecruss.com
-----------------------------	---